

# LTRN023NW

Illuminatore circolare a LED, diametro interno 28 mm, luce diretta, bianca

## CARATTERISTICHE

### Specifiche ottiche

Colore luce, lunghezza d'onda di picco		white
Optimal working distance	(mm)	55-85
Illuminance at minimum working distance	(lux)	25700
Illuminance at maximum working distance	(lux)	15000

### Lighting area diameter

Outer	(mm)	90
Inner	(mm)	32

### Specifiche elettriche

Number of LED rows		1
--------------------	--	---

### Continuous mode 1

Supply voltage	(V)	24
Current	(mA)	480
Power consumption	W	11.52

### Pulsed mode

Supply voltage 2	(V)	24-48
Max pulse current 3	(mA)	1440
Max. trigger pulse duration	(ms)	10
Duty cycle	(%)	0-10%

### Specifiche meccaniche

Diametro esterno	(mm)	104
Diametro interno	(mm)	28
Altezza	(mm)	40
Massa	(g)	350
Cooling method	Attached to machine part for better heat dissipation	

### Compatibilità

Prodotti compatibili	TC2300x, TC23012, TC4M00x, MC3-03X
----------------------	------------------------------------

## NOTE

1. Longevità: 20.000 ore (calo di intensità del 50%) a 25° C
2. Raccomandata a 36 V.
3. A corrente di pilotaggio costante

